Vifoam 120





Main Office, R&D and Logistics

Avenida do Polo 3, nº159, 4590-137 Carvalhosa Paços de Ferreira - Portugal Tlm . +351 917 851 019

Office

Rua Quinta do Bom Retiro nº16, Armazém 9 2820-690 Charneca da Caparica - Portugal Tel. +351 212 964 100 Fax. +351 212 964 101

Vicoustic USA

5701 Sixth Avenue South, Suite 229 Seattle, WA 98108 Tel . (206) 767-2020 E-mail . info@vicousticusa.com

www.vicousticusa.com

Vifoam offers both absorption and simplicity. Mostly used in the construction of buildings and suspended ceilings, it provides an excellent replacement for mineral wool in cases where health and safety are paramount.

Available in two sizes; 120 x 60 x 4 cm and 60 x 60 x 4 cm.

ApplicationsListening Rooms, Home Theaters, Recording and Broadcast Studios, Post Production Studios, Performance Spaces, Rehearsal Rooms, Conference and Teleconference Rooms, Public Spaces, Auditoriums, suspended ceilings, behind multi perforated boards, multi perforated gypsum boards, etc.

Main Info Ref: B00449

EAN13: 5600301840111 HS Code: 39211310

Dimensions: 1200 x 600 x 40 mm

Performance Fire Class France (NF P): M1

Shipping Units per Box: 10

Box Dimensions: 1200.0 x 600.0 x 600.0 mm

Technical File