



Apollo Monoblock Amplifiers

Elegant and refined, yet brutally powerful, Rogue Audio's flagship monoblock amplifiers have raised the bar for reference level amplification. The Apollo's ability to reveal the finest musical details while providing seemingly limitless dynamics are the hallmark of the finest amplifiers we have ever produced. Whether your passion is jazz, rock or symphonic works, these amplifiers will provide the clarity and dynamics to closely rival the original performance.

That these pure tube amplifiers boast a continuous power output of over 250 watts is but a small part of the story. Designed and engineered without compromise, the Apollos boast ruler flat frequency response, tremendous bandwidth, huge dynamic range, and vanishingly low levels of distortion. And the enormous LC power supplies enable the reproduction of musical transients at far beyond the amplifier's rated output. With a unique and tasteful appearance, the Apollo chassis' are constructed using CNC machined aluminum faceplates and body panels. The ultra-high tolerance electronics components and huge transformers contribute to the peerless build quality. Features include an on-the-fly switch offering either Triode or Ultralinear operation. A second standby switch allows the amplifier to remain warmed up and ready for immediate use between listening sessions. A built in meter and individual bias switches makes tube biasing a snap even for the tube novice. The rear panel contains balanced and single ended inputs as well as 4 and 8 ohm Cardas binding posts.

General Features:

- Monoblock design for perfect channel separation
- Massive high storage LC power supply
- Ultra-high performance transformers
- Built in bias meters and bias tool
- All precision components
- 6 x KT120, 2 x 12AU7, 1 x 12AX7 tubes per amp
- CNC machined aluminum chassis
- Heavy-duty gold plated RCA connectors
- Heavy-duty gold plated binding posts
- Balanced (XLR) and RCA inputs
- Both 4 and 8 ohm binding posts
- User selectable triode/ultralinear output
- Fully tested, burned-in, and auditioned
- Entirely designed and built in the USA

Specifications:

- Output power: 250 WPC
- THD: less than 0.1% typical, 1% at peak
- frequency response:
- 20Hz -25KHz at full output
- 10Hz -100KHz at 10 watts
- Input sensitivity: 1.0V RMS
- Dimensions: 9.5" W x 24.5" D x 12" H
- Weight: 100 lbs each
- Power requirements: 115V/230V – 50/60Hz

